

# HOME RANGE | SPLIT 1x1

## AROMA 2E

**3 YEARS**  
WARRANTY  
**TOTAL**  
QUALITY COMMITMENT

**10 YEARS**  
WARRANTY  
**COMPRESSOR**  
QUALITY COMMITMENT

**21dB**  
DEPENDENT ON MODEL


**A++**  
SEER

**A+**  
SCOP

**A+++**  
SCOP  
Warmer

## Enjoy the comfort

With the Aroma 2E split you will be able to live the best comfort, with its triple filter you will eliminate bad odors and small particles, also thanks to its included Wi-Fi you will be able to control all the functions wherever you are.



**TRIPLE  
FILTER**

**10 YEARS**  
WARRANTY  
COMPRESSOR

**SERIE AROMA**  
giatsu  
**RELIABILITY**  
SINCE 2017



### Clean Air

Includes Cold Catalyst, Silver Ion and Activated Carbon filters to eliminate bad odors and particles.




### Wifi Included

You can control the equipment from a smartphone, tablet or by voice with Alexa and Google Home.

### CONNECTA+

### Optional Conecta+

Special plate for automatic ON/OFF switching of the air conditioning in hotel cards, tourist flats or window sensors.



### Versatility

Supports long installation distances: 50 m distance and 25 m drop (for 7.1 kW model).



### Service life

The coils of the indoor and outdoor unit have Golden Fin protection, an anticorrosive for saline environments that extends their durability.



### Comfort

With the "I Feel" function, the split takes as the reference temperature of the room the one with the remote control.



### Efficient

Energy classification A++ in cooling and A+++ in heating for hot areas.



**TRIPLE  
FILTER**

SPLIT 1X1  
**AROMA 2E**

**CONNECTA+**  
Optional



| MODELS                  | INT.   | GIA-S09AR2E-R32                          | GIA-S12AR2E-R32   | GIA-S18AR2E-R32   | GIA-S24AR2E-R32   |
|-------------------------|--------|------------------------------------------|-------------------|-------------------|-------------------|
|                         | EXT.   | GIA-S09AR2E-R32-I                        | GIA-S12AR2E-R32-I | GIA-S18AR2E-R32-I | GIA-S24AR2E-R32-I |
|                         |        | GIA-S09AR2E-R32-O                        | GIA-S12AR2E-R32-O | GIA-S18AR2E-R32-O | GIA-S24AR2E-R32-O |
| EAN CODE                |        | 8435483854017                            | 8435483853980     | 8435483854413     | 8435483854444     |
| Electrical power supply | V,F,Hz | 220-240V (1 Phase ~ 50Hz) / Outdoor unit |                   |                   |                   |

#### PERFORMANCE

|                  |                    |       |                       |                       |                       |                       |
|------------------|--------------------|-------|-----------------------|-----------------------|-----------------------|-----------------------|
| Cooling capacity | Capacity           | kW    | 2,64 (1,00-3,40)      | 3,5 (1,11-3,92)       | 5,28 (1,99-6,73)      | 7,03 (2,08-7,92)      |
|                  |                    | Btu/h | 9.000 (3.100-11.600)  | 12.000 (3.800-13.400) | 18.100 (6.800-2.300)  | 23.900 (7.100-27.000) |
|                  | Consumption        | W     | 800(100-1240)         | 1320(83-1600)         | 1550 (140-2300)       | 2600 (420-3150)       |
|                  | Current            | A     | 3,48                  | 5,8                   | 6,7                   | 11,5                  |
|                  | SEER               | W/W   | 7                     | 6,5                   | 7,4                   | 6,1                   |
|                  | Energy class       | Cold  | A++                   | A++                   | A++                   | A++                   |
| Heating capacity | Annual consumption | kWh   | 130                   | 188                   | 247                   | 405                   |
|                  | Capacity           | kW    | 2,93 (0,84-3,37)      | 3,81 (1,09-4,17)      | 5,57 (1,29-6,74)      | 7,33 (1,62-7,92)      |
|                  |                    | Btu/h | 10.000 (2.800-11.500) | 13.000 (3.700-14.200) | 18.800 (4.400-23.000) | 24.900 (5.500-27.000) |
|                  | Consumption        | W     | 930 (120-1.200)       | 1.190 (167-1.400)     | 1.570 (220-2350)      | 2.400 (300-2.750)     |
|                  | Current            | A     | 4,05                  | 5,3                   | 6,8                   | 11                    |
|                  | SCOP               | W/W   | 4,1                   | 4,1                   | 4,0                   | 4,0                   |
| Features         | Energy class       | Heat  | A+                    | A+                    | A+                    | A+                    |
|                  | Annual consumption | kWh   | 792                   | 957                   | 1435                  | 1680                  |

#### FEATURES

|              |                          |        |               |                   |               |                 |
|--------------|--------------------------|--------|---------------|-------------------|---------------|-----------------|
| Indoor unit  | Sound power (H/M/L/S)    | dB     | 50            | 54                | 56            | 59              |
|              | Sound pressure (H/M/L/S) | dB     | 37/32/25/21,5 | 39,5/35,5/25/21,5 | 42,5/36/26/20 | 45/40,5/36/29,5 |
|              | Air flow (H/M/L/S)       | m³/h   | 435/333/259   | 530/430/310       | 840/680/540   | 980/817/662     |
|              | Temperature range        | °C     | 17-32/0-30    | 17-32/0-30        | 17-32/0-30    | 17-32/0-30      |
| Outdoor unit | Sound power              | dB     | 59            | 64                | 63            | 67              |
|              | Sound pressure           | dB     | 55            | 55                | 56            | 59              |
|              | Air flow                 | m³/h   | 1750          | 1750              | 2100          | 3500            |
|              | Operating temperature    | °C     | -15-50/-20-30 | -15-50/-20-30     | -15-50/-20-30 | -15-50/-20-30   |
| Refrigerant  | Compressor               | Type   | ROTARY        | ROTARY            | Rotary        | Twin-rotary     |
|              |                          | Brand  | GMCC          | GMCC              | GMCC          | GMCC            |
|              | Type/Charge              | R32/kg | 0,47          | 0,52              | 1,08          | 1,42            |
|              | Carga adicional          | g/m    | 12            | 12                | 12            | 24              |

#### DIMENSIONS AND WEIGHT

|              |                          |    |             |             |              |              |
|--------------|--------------------------|----|-------------|-------------|--------------|--------------|
| Indoor unit  | Net dimensions (W×H×D)   | mm | 715x194x285 | 805x194x285 | 957x302x213  | 1040x327x220 |
|              | Gross dimensions (W×H×D) | mm | 780x270x365 | 870x270x365 | 1035x385x295 | 1120x405x315 |
|              | Net/Gross weight         | kg | 6,7/8,8     | 7,3/9,5     | 10/13        | 12,3/15,8    |
| Outdoor unit | Net dimensions (W×H×D)   | mm | 720x270x495 | 720x270x495 | 805x554x330  | 890x673x342  |
|              | Gross dimensions (W×H×D) | mm | 835x300x540 | 835x300x540 | 915x615x370  | 995x740x398  |
|              | Net/Gross weight         | kg | 21/22,8     | 21/22,8     | 32,7/35,4    | 42,9/45,9    |

#### CONNECTIONS

|                      |                 |     |         |         |         |         |
|----------------------|-----------------|-----|---------|---------|---------|---------|
| Refrigeration pipe   | Liquid - Gas    | in. | 1/4-3/8 | 1/4-3/8 | 1/4-1/2 | 3/8-5/8 |
|                      | Max. length     | m   | 25      | 25      | 30      | 50      |
|                      | Max. elevation  | m   | 10      | 10      | 20      | 25      |
| Electric connections | Power supply    | mm  | 2x2,5+T | 2x2,5+T | 2x2,5+T | 2x2,5+T |
|                      | Interconnection | mm  | 4x2,5+T | 4x2,5+T | 4x2,5+T | 4x2,5+T |

#### Notes:

Capacity data in standard conditions. Actual data will vary depending on where the equipment is installed and how it is used.  
The dimensions of the electrical wiring are approximate, they should be calculated according to the conditions of the installation itself.